




推入式铆钉/子母扣

增大的头部设计可以作为把手非常方便快捷地拔出
压入即可安装到位。高效，可靠，绝缘，无磁
材料 尼龙 66，颜色黑色，自然色两种可选



底座膨胀一字型

底座膨胀十字型



紧固总厚度

安装孔径



黑色	白色		A	B	C	D	E	F	G	图例
20573	20574	SRT-3035B	10.0	8.0	3.5	3.0	6.6	1.0-2.0	3.1-3.2	1
20575	20576	SRT-3045B	10.0	8.0	4.5	3.0	6.6	2.0-3.0	3.1-3.2	1
20577	20578	SRT-3055B	10.0	8.0	5.5	3.0	6.6	3.0-4.0	3.1-3.2	1
20579	20580	SRT-3065B	10.0	8.0	6.5	3.0	9.0	4.0-5.0	3.1-3.2	1
20581	20582	SRT-3075B	10.0	8.0	7.9	3.0	9.0	5.0-6.0	3.1-3.2	1
20583	20584	SRT-3080B	10.0	8.0	8.0	3.0	9.0	5.5-6.5	3.1-3.2	1
20585	20586	SRT-3535B	10.0	8.0	3.5	3.5	6.6	1.0-2.0	3.6-3.7	2
20587	20588	SRT-3545B	10.0	8.0	4.5	3.5	6.6	2.0-3.0	3.6-3.7	2
20589	20590	SRT-3555B	10.0	8.0	5.5	3.5	6.6	3.0-4.0	3.6-3.7	2
20591	20592	SRT-3560B	10.0	8.0	6.0	3.5	9.0	3.5-4.5	3.6-3.7	2
20593	20594	SRT-3570B	10.0	8.0	7.0	3.5	9.0	4.5-5.5	3.6-3.7	2
20595	20596	SRT-3580B	10.0	8.0	8.0	3.5	9.0	5.5-6.5	3.6-3.7	2
20597	20795		10.0	8.0	5.0	4.0	7.6	2.5-3.5	4.1-4.2	2
20598	20600	SRT-4050B	12.0	8.0	5.0	4.0	7.6	2.5-3.5	4.1-4.2	2
20601	20602	SRT-4060B	12.0	8.0	6.0	4.0	7.6	3.5-4.5	4.1-4.2	2
20603	20604	SRT-4070B	12.0	8.0	7.0	4.0	11.2	4.5-5.5	4.1-4.2	2
20605	20606	SRT-4080B	12.0	8.0	8.0	4.0	11.2	5.5-6.5	4.1-4.2	2
20607	20609	SRT-4090B	12.0	8.0	9.0	4.0	11.2	6.5-7.5	4.1-4.2	2
20610	20611	SRT-4100B	12.0	8.0	10.0	4.0	11.2	7.5-8.5	4.1-4.2	2

