

物料编号	长度L inch.	长度L MM	宽 W MM	捆扎范围 Bundle Diameter MM	拉力强度最小 Tensile Strength	拉力强度最小 Tensile Strength KGS
CTI050	53.1"	1350	9.0	10-380	175.0	88.0
CTI051	24"	600	12.0	6-170	180.0	83.0
CTI052	25.6"	650	12.0	6-165	180.0	83.0
CTI053	17.8"	450	12.7	10-125	250.0	114.0
CTI054	19.6"	500	12.7	12-150	250.0	114.0
CTI055	11.8"	300	12.7	12-105	250.0	114.0
CTI056	15.8"	400	12.7	12-155	250.0	114.0
CTI057	21.2"	540	12.7	14-190	250.0	114.0
CTI058	30.7"	780	12.7	14-230	250.0	114.0
CTI059	21.2"	540	13.0	14-155	250.0	114.0


1. MATERIAL NYLON 66

2. STANDARD COLOUR NATURE.
BLACK COLOUR IS AVAILABLE
BY ADDING SUFFIX CODE "BK"

3. FLAMMABILITY : UL94V2
UL94V0 IS AVAILABLE
BY ADDING SUFFIX CODE "V0"

4. OPERATING TEMPERATURE RANGE: -40°C TO 85 °C
HIGH TEMPERATURE(110 °C) IS AVAILABLE
BY ADDING SUFFIX CODE"HT"

5. MAXIMUM WIRE BUNDLE:SEE TABLE



MIn. Loop tensile strength

 <i>industrial fastening components</i>		ALL DIMENSIONS IN mm GENERAL TOLERANCES ± 0.25 UNLESS OTHERWISE STATED 1 DECIMAL PLACE ± 0.25 2 DECIMAL PLACES ± 0.10 ANGULAR $\pm 1^\circ$		THIRD ANGLE 	
MATERIAL: POLYAMIDE 6/6			COLOUR: SEE TABLE		
DESCRIPTION: CABLE STRAP			PART No: SEE TABLE		
DRG No: 012-006		PROJECT NUMBER: EU12-0020		Mass:(g)	SHEET SIZE A4
DRN SFH	DATE 03/02/12	CHKD TC	DATE 03/02/12	SCALE NTS	SHEET No. 1 OF 1