	A B	С	D			E		F		_	
	THIS DOCUMENT IS THE PROPERTY OF SINOHUA ENGINEERING SOLUTIONS. THE CONTENTS ARE CONFIDE					REV.	MODIFICATION.	DATE	DRN		
	NEITHER THIS DOCUMENT NOR ITS CONTENT SHALL BE DISCLOSED TO ANY UNAUTHORIZED PERSON, CO	IED OR PUBLISHED WITHOUT SINOHU	A ENGINEERING SOLUTIONS	PRIOR WRITTEN C	ONSENT.	01 P	RODUCTION RELEAS	E 02/02/16	SFH		
		Dotatable		ato						1	
	Rotatable Mounts										
			<b>A</b>							-	
		/									
		// 1.	23			ı— —ı — -					
		(3)	1.2)							2	
					- T						
			↓								
			<b>V</b>								
	1.64					0.73	_				
	(41.7)					18.5)					
3		I				,	I			3	
	_										
	DSWS5CN										
							ALL DIMENSION GENERAL TOLE		THIRD		
-	. The two mounts are accurate factored together with a connecting	<ul> <li>Separates bundles to avoid</li> </ul>	debrasion		Sini	<b>]HII</b>	UNLESS OTHERV 1 DECIMAL PLA	/ISE STATED CE ±0.25	ANGLE	-	
	<ul> <li>The two mounts are securely fastened together with a connecting rivet that allows both mounts to rotate</li> </ul>	Material: Weather Resistar		i	industrial fas	tening comp	2 DECIMAL PLA	CFS + 0.10 /	$\oplus$	-	
	<ul> <li>Can join bundles of cable, tubing, or hoses that may need to move or are not parallel</li> </ul>	Colour Black			MATERIAL:		·	COLOUR:		1	
		Max strap width 12.7mm			SEE TABLE DESCRIPTION:			PART NO:	BLE	-	
		Pull apart force 112 kg			HEAV	SEE TAB	LE	4			
							PART NUMBER:	Mass:(g)	SHEET SIZE	1	
				-	DSWS		563398	SCALE	A4	-	
					drn SFH	date 03/02/12	Снкр рате 2 TC 03/02/1		sheet No. 1 OF 1		
L	A B	С	D			E		FORM	No. 0145/16	1	