

REV.	MODIFICATION.	DATE	DRN
01	PRODUCTION RELEASE	02/02/16	SFH

物料编号	适合安装板厚	建议钣金开孔直径	材料	穿线孔直径毫米 A	护线套外径毫米 B	总厚度毫米 C
SRG1022	4.8	7,9	SBR	4,8	11,8	8,0
SRG1034	4.8	9,5	SBR	4,8	15,9	9,5
SRG1057	4.8	11,1	SBR	6,4	15,9	8,0
SRG1110	4.8	14,3	Nitrile	4,8	19,1	8,0
SRG1115	4.8		SBR	8,0	20,7	9,5
SRG1116	4.8		SBR	8,0	20,7	11,1
SRG1120	4.8		SBR	9,5	20,7	9,5
SRG1133	4.8	15,9	SBR	9,5	22,2	11,1
SRG1135	4.8		Nitrile	10,2	27,9	
SRG1153	4.8	17,5	SBR	11,1	23,8	
SRG1172	4.8	19,1	SBR	8,0	25,4	
SRG1194	4.8	20,6	SBR	12,7	27,0	
SRG1199	4.8		SBR	14,3		
SRG1213	4.8	22,2	SBR	14,3	27,0	
SRG1219	4.8		SBR	15,9	28,6	
SRG1256	4.8	25,4	SBR	17,5	33,4	12,7
SRG1261	4.8		SBR	19,1	31,8	14,3
SRG1272	4.8	27,0	SBR	19,1	34,9	12,7
SRG1306	4.8	31,8	SBR	22,2	41,3	14,3
SRG1312	4.8		SBR	25,4	38,1	11,1
SRG1323	4.8	34,9	SBR	25,4	44,5	14,3
SRG1329	4.8		SBR	28,6	47,6	12,7
SRG1351	4.8	38,1	EPDM	31,8	50,8	15,9
SRG1372	4.8	44,5	SBR	38,1	54,0	14,3
SRG1390	4.8	50,8	SBR	41,3	57,2	19,1
SRG1404	4.8	55,9	SBR	50,8	69,9	14,2
SRG1414	4.8	60.3	EPDM	50,8	69,9	

- **Used to protect through holes.**
Help eliminate sharp edges so your wires are protected and add aesthetic value to your application.
- Provide vibration dampening.

