
REV.	MODIFICATION.	DATE	DRN
01	PRODUCTION RELEASE	02/02/16	SFH

SPACING "A"	Article #
3.2	DLPCBS101
4.0	DLPCBS102
5.0	DLPCBS103
6.4	DLPCBS104
7.0	DLPCBS105
8.0	DLPCBS106
9.5	DLPCBS107
11.1	DLPCBS108
12.0	DLPCBS109
15.0	DLPCBS110
15.9	DLPCBS111
17.0	DLPCBS112
20.2	DLPCBS113
22.2	DLPCBS114
25.4	DLPCBS115

**Top Hole:** 3.0±0.08mm **Panel Thickness:** 1.20-1.98mm



Bottom Hole: 3.0±0.08mm

Panel Thickness: 1.20-1.98mm

## **NOTES**

- 1. MATERIAL PA66, NATURE
- 2. FLAMMABILITY UL94 V2 STANDARD OPTION.
- 3. WORKING TEMPERATURE MIN -40°C MAX 85 °C



ALL DIMENSIONS IN mm

1 DECIMAL PLACE ±0.25 2 DECIMAL PLACES ± 0.10 ANGULAR ±1°



DESCRIPTION:

## **DUAL LOCKING PCB SPACERS**

MATERIAL:			COLOUR:		PART No:	
SEE NOTES			SEE TABLE		SEE TABLE	
DRG No: PROT-M12		PROJECT NUMBER: DLPCBS1XX		Mass:(g)	SHEET SIZE	
	PROT-I	M12	DLF	PCBS1XX		A4
	PROT-I DRN SFH	DATE 03/02/12	CHKD TC	DATE 03/02/12	scale NTS	A4 SHEET No. 1 OF 1

FORM No. 0145/16