







CLOSE TYPE



OPEN TYPE



LONG TYPE

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LL 12/04/06'		

NOTES:

1. SPECIFICATION:

- 1.1 CONTACT RESISTANCE: 30mΩ MAX.
- 1.2 DIELECTRIC WITHSTANDING VOLTAGE: 250V AC(rms) FOR 1 MINUTE.
- 1.3 INSULATION RESISTANCE: 500MΩ Min.
- 1.4 OPERATING TEMPERATURE: -20°C~+80°C.

2. PRODUCT NUMBER CODE:

MJL254 X X X X X

PROFILE HEIGHT(DIM A):
0:6.0mm
1:6.47mm

CONTACT PLATING:
F1: FULL GOLD FLASH
N: NICKEL
2: GOLD+NICKEL

HOUSING COLOR:
B: BLACK U:BLUE Y:YELLOW
W: WHITE E:GREEN R:RED

HOUSING TYPE:
A:OPEN B:CLOSE L:Long

No.OF CONTACTS:
2: 2pin

SERIES No:
MJL254

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

PROJECTION	
UNITS	mm
SHEET SIZE	A4

MINI JUMPER PITCH 2.54mm

www.sinohua.cn

2	HOUSING		PBT	SEE NOTES	DRAWING TYPE	CUSTOMER		
1	CONTACT		COPPER ALLOY	SEE NOTES	SCALE	1:1	SHEET	1 OF 1
ITEM	PART NAME	PART NO.	MATERILAS	FINISHED	DRAWING NO.	C-DS1027-XXXXX		

