


Plastic Hose Clamps

尺寸 (mm)

Article#	clamping diameter	W
1350100	5.6 - 6.5	4.2
1350101	6.6 - 8.0	5.0
1350102	8.0 - 9.2	5.0
1350103	9.2 - 10.5	5.0
1350104	10.5 - 12.0	6.0
1350106	12.8 - 15.0	7.0
1350107	15.0 - 17.2	7.0
1350108	17.0 - 18.5	7.0
1350109	18.2 - 20.5	7.0
1350110	20.5 - 23.0	7.0
1350111	22.0 - 25.0	7.0
1350112	25.0 - 28.0	7.0
1350113	27.0 - 30.0	7.5
1350114	29.5 - 32.5	7.5
1350115	32.5 - 35.5	8.0
1350116	35.0 - 38.5	8.0
1350117	38.0 - 41.5	8.0
1350118	41.0 - 44.5	8.0
1350119	44.0 - 47.5	8.0
1350120	47.0 - 50.5	8.0
1350121	50.0 - 53.5	8.0
1350122	53.0 - 57.0	8.0
1350123	56.5 - 60.5	8.0
1350124	60.0 - 65.0	8.0
1350125	66.0 - 70.0	8.0
1350126	70.0 - 75.0	8.0
1350127	76.0 - 80.0	8.0
1350128	80.0 - 85.0	8.0



Nylon Ratchet Hose Clamps are based on the original design for this type of fastener.

An overlapping tapered ring of nylon is fastened around the hose or tubing desired and secured to the required tightness by compressing interacting grooves in a ratcheting fashion, creating a tight sealing application. Clamps are reusable.

They can be removed by separating the clamping halves in a perpendicular direction at the seal.